



Fusion Carpet Base

CARPET BASE	Oxygen, Selenium, Cobalt, Xenon
CONSTRUCTION	Patterned Cut and Loop
FIBER	100% BCF Nylon, type 6,6
DYE METHOD	Injection dyed (print)
GAUGE	1/10 in (39.4 /10 cm)
STITCH COUNT	12.0 stitches / in (47.5 / 10 cm)
PILE WEIGHT (AVERAGE)	36 oz / y ² / (1220 g / m ²)
PILE HEIGHT (AVERAGE)	0.295 in (7.5 mm)
DENSITY FACTOR	4309
WIDTH	12 feet (3.66 m)
PRIMARY BACKING	Woven polypropylene
SECONDARY BACKING	Action Bac
STATIC CONTROL	Less than 3.5 kV
FLAMMABILITY	Meets C.G.S.B. 4-GP-129
FLOORING RADIANT PANEL	Class 1 (ASTM E-648)
SMOKE DENSITY	Less than 450 (ASTM E-662)
SOIL PROTECTION	Commercial Soil Protection
STAIN RESISTANCE	Commercial Stain Protection
INDOOR AIR QUALITY	GLP 1318 Green Label Plus
ISO CERTIFICATION	Made in an ISO 9002 and ISO 14001 certified facility
LIMITED WARRANTY	10-year Wear

Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances. Components may be changed without notice due to raw material shortages and/or technological advances. Such variances do not affect performance.

Color may vary from one dye lot to another.

For more details, please contact your sale representative. 1.888.467.5075